

eritage Collection

INSTALLATION INSTRUCTIONS

SPECIFICATIONS

Zorouty® Stair Rods slide into each bracket approximately 1/3". Finials attach to the bracket, not the rod.

FINIAL	LENGTH
Pineapple	1 2/42
Round	3/4"
Crown	1 7/6*
Urn	1 1/4"
Acom	1 1/4"
ROD GAUGE: ROD DIAMETER:	.031" 1/2"


Also available as a "Chasic Bracket" without finial and without side holes.


ALWAYS USE A SCHOOLSLIP PAR AND COM-ANOTHER MEANS OF INSTALLATION, STAIR RODS ALONE ARE NOT A FORM OF CARPET INSTALLATION.

ALL PARTS ARE LACQUER COATED TO RESIST TARKSHING, DO NOT USE BRASS CLEANER OR OTHER ABRABIVES. TO CLEAN. SIMPLY WIPE WITH A SOFT DRY CLOTH.

PERIODICALLY CRECK AND TIGHTEN ALL SCREWS AND WARDWARE.

REGULAR







- 1. The carget runner must be installed using another method of installation. Zoroufy Stair Roch are for decorative use only.
- 2. If fimals have been selected, attach fimals to the brackets using small screws provided in finials.
- 3. Locate desired position of the brackets by inserting the rod into the brackets and laying on the stairs. Positioning both the left and right bracket an equal distance from the side edges of the runner is the most preferable position.
- 4. Open the swing latch covers of the brackets exposing the matallation screw holes.
- 5. For each step, install one bracket onto stairs using screws provided or other anchors suitable for stair material. Drilling a pilot hole first is recommended. Insert the rod into the installed bracket and place remaining bracket on the other end to confirm exact position of the bracket on the other side.
- Install remaining bracket using the same method as above.

